# <u>SAFETY DATA SHEET</u>

**Product:** 60P Acrylonitrile-Butadiene-Styrene Copolymer Page: 1 / 7

Version: 2.0 Date: 31/12/2021

## 1.PRODUCT AND COMPANY INDENTIFICATION

#### PHONE NUMBERS

Emergency Medical (24 HOUR) 886-7-3513911
Emergency Transportation / CHEMTREC (24 HOUR) 886-7-3513911
Other Emergency Information (24 HOUR) 886-7-3513911
Non-Emergency Information 886-7-3513911

## PRODUCT IDENTIFICATION

PRODUCT IDENTIFIER: ABS 60 Powder (60P)

PRODUCT DESCRIPTION: acrylonitrile butadiene styrene copolymer

PRODUCT USE: May be used to produce molded or extruded articles or as a component of other

industrial products.

## 2. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

- Fine particle powder with slight or no odor.
- Spilled material may create slipping hazard.
- Can burn in a fire creating dense toxic smoke.
- Molten plastic can cause severe thermal burns.
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

HMIS Ratings: Health = 0; Flammability = 1; Reactivity-0, PPE-B

#### POTENTIAL HEALTH EFFECTS

INGESTION: No hazard in normal industrial use.

SKIN ABSORPTION: No absorption hazard in normal industrial use.

EYE CONTACT: Can cause mechanical irritation if dusts are generated.

SKIN CONTACT: May cause skin irritation.

## CHRONIC/CARCINOGENICITY

NTP: Not Tested.

OSHA: Not Regulated.

**Product: 60P** Acrylonitrile-Butadiene-Styrene Copolymer

Version: 2.0

Page: 2 / 7

Date: 31/12/2021

IARC: Not Listed.

MEDICAL RESTRICTIONS: There are no known human health effects aggravated by exposure

to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by

exposure to components in the processing vapors.

#### 3. COMPOSITION/INF ORMATION ON INGREDIENTS

## 3.1 Composition of the substance

Components listed below are physical or health hazards as defined in the Hazard Communication Standard. The quantities represent typical or average values for the materials shown. Additional compositional data are provided in Section 15. REGULATORY INFORMATION, subject to supplier notification requirements.

Component Name	%	CAS Number	ACGIH TWA
ABS Powder	100	9003-56-9	None

## 3.2Additional information:

## REACH info.

Substance name	Registration NO.
Acrylonitrile	01-2119474195-34-0050
1,3-Butadiene	01-2119471988-16-0044
Styrene	01-2119457861-32-0007

## 4. FIRST AID MEASURES

EYES: case of pellets or powder, flush with plenty of water for at least 15 minutes. Seek medical advice if any dust particles still remain. In case of gases evolving from melted resin of high temperature, flush with plenty of water for at least 15 minutes. Seek medical advice if necessary..

SKIN: In case of pellets or powder, wash with water. In case of melt, wash affected skin area and clothing with plenty of (soap and) water. Seek medical advice.

INGESTION: In case of gases evolving from melted resin, move subject to fresh air. Treat symptomatically.

**Product: 60P** Acrylonitrile-Butadiene-Styrene Copolymer Version: 2.0

ion: 2.0 Date: 31/12/2021

Page: 3 / 7

## **5.FIRE FIGHTING MEASURES**

FIRE FLGHTING: Do not enter fire area without proper protection including self contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

EXTINGUISHING MEDIA: Water spray and foam. Carbon dioxide and dry chemical arc not recommended because their lack of cooling capacity may permit re ignition.

HAZARDOUS COMBUSTION PRODUCTS: Intense heat, smoke, carbon dioxide, carbon monoxide, hydrocarbon fragments.

CONDITIONS OF FLAMMABILITY: Requires a continuous flame source to ignite.

#### 6. ACCIDENTAL RELEASE MEASURES

GENERAL: No special spill clean-up considerations. Collect and discard in regular trash.

Warning! Avoid the generation of dusts during clean-up. Allow molten material to solidify before disposal.

## 7. HANDLING AND STORAGE

HANDLING: No special handling instructions due to toxicity.

STORAGE: store between 5~55°C. Keep covered when not use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended. Processing fumes condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, duct work, and other surfaces using appropriate personal protection.

Local ventilation requirements must be determined to limit exposure to processing fumes in the workplace.

## PERSONAL PROTECTION

EYE/FACE: Wear safety glasses with side shields or chemical goggles. In addition, use full face shield when cleaning processing fume condensates from hoods, ducts, and other surfaces.

**Product:** 60P Acrylonitrile-Butadiene-Styrene Copolymer

Version: 2.0 Date: 31/12/2021

Page: 4 / 7

SKIN: When handling pellets or powder, avoid prolonged or repeated contact with skin. Wear long pants, long sleeves, well insulated gloves, and a face shield during melt processing. Appropriate clothing-including chemical resistant gloves-should be worn to prevent contact with processing fumes condensate.

RESPIRATORY: When using this product at elevated temperatures, implement engineering systems, administrative controls, or a respiratory protection program (including a respirator approved for protection from organic vapors, acid gases, and particulate matter) if processing fumes are not adequately controlled or operators experience symptoms of overexposure. If dust or powder are produced from secondary operations such as sawing or grinding, use a respirator approved for protection from dust.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Powder

ODOR AND APPEARANCE: Plastic powder with slight odor.

COLOR: White

MELTING POINT: This product does not exhibit a sharp melting point but softens gradually

over a wide range of temperatures.

VAPOR PRESSURE(mmHg): None

**VAPOR DENSITY**: None

2

BULK DENSITY( $g/cm^3$ ) : <1

WATER SOLUBILITY: Insoluble in water

## 10. STABILITY AND REACTIVITY

STABILITY: Stable

REACTIVITY: Net reactive under recommended conditions of handling, storage, processing

and use.

CONDITIONS TO AVOID: Non-reactive.

## 11. TOXICOLOGICAL INFORMATION

**Product: 60P** Acrylonitrile-Butadiene-Styrene Copolymer Version: 2.0

Date: 31/12/2021

Page: 5 / 7

## **ACUTE HEALTH HAZARDS**

EYE CONTACT: Product not considered primary eye irritant. When similar products, in finely divided form, were placed into the eyes of rabbits, slight transient redness or discharge occurred. This is consistent with the expected slightly abrasive nature of the resin particles.

SKIN CONTACT: Product not considered primary skin irritant.

SUBCHRONIC HEALTH HAZARDS

SUBCHRONIC TOXICITY: No data available.

CHRONIC HEALTH HAZARDS

**CARCINOGENIC** 

NTP: Not Tested.

OSHA: Not Regulated.

LARC: Not Listed.

## 12. ECOLOGICAL INFORMATION

GENERAL: This material is not expected to be harmful to the ecology.

## 13. DISPOSAL INFORMATION

WASTE DISPOSAL: Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fumes condensates and incinerator ash should be tested to determine waste classification.

POSSTBLEEPA WASTE CODES: No data.

#### 14. TRANSPORTATION INFORMATION

REGULATORY STATUS: NOT RESTRICED IATA DGR 60 EDITION.

## 15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT(TSCA): This product is in compliance with all rules and orders of TSCA.

WHMIS PRODUCT CLASSIFICATION: Not a controlled product.

### 16. OTHER INFORMATION

Prepared by: Product Stewardship



**Product:** 60P Acrylonitrile-Butadiene-Styrene Copolymer

Version: 2.0

Page: 6 / 7
Date: 31/12/2021

DISCLAIMER: This Safety Data Sheet [SDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. Does not warrant the suitability for use of this SDS for any other material or product not specifically identified herein. Does not warrant the accuracy or authenticity of this SDS unless it has been obtained directly from GPPC, or posted or viewed on a website. Modification of this SDS, unless specifically authorized by GPPC, is strictly prohibited. This SDS is based on information which is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. GRAND PACIFIC PETROCHEMICAL CORPORATION MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

## ABBREVLATIONS:

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

**CPR**: Cardiopulmonary Resuscitation

EPA: Environmental Protection Agency

HMIS: Hazardous Material Identification System (National Paint and Coatings Association)

IARC: International Agency for Research on Cancer

NTP: National Toxicology Program

PPE: Personal Protective Equipment

TLV: Threshold Limit Value

TSCA: Toxic Substance Control Act

**Product:** 60P Acrylonitrile-Butadiene-Styrene Copolymer

Version: 2.0 Date: 31/12/2021

Page: 7 / 7

WHMIS: Workplace Hazardous Materials Information System (Canada)